

SAFETY LABEL

Manufacturer: NORSK KLEBER
 Skansen 29, Otta, Norway
Model: MARCELLO
Variant:
Serial:
Date of Manufacture:
Tested To: UL 1482-2011 (R2015)
ULC-S6270-00 (R2016)

NOT APPROVED FOR USE IN MOBILE HOMES
Install and Use in Accordance with Norsk Kleber Installation and Assembly Instructions only
FOR USE WITH SOLID WOOD FUEL ONLY.
Do Not Connect This Unit to a Chimney Flue Serving Another Appliance
Inspect and Clean Chimney Frequently-Under Certain Conditions of Use, Creosote Buildup



CAUTION

HOT WHILE IN OPERATION DO NOT TOUCH, KEEP CHILDREN, CLOTHING AND FURNITURE AWAY MAY CAUSE SKIN BURNS SEE NAME PLATE AND INSTRUCTIONS

PREVENT HOME FIRES: Contact Local Building and Fire Officials About restrictions in your Area.
NORSK KLEBER requires installation and assembly by trained professionals only.



File Number: 19-515

Minimum Clearances to Combustible Materials

SW	Side Wall to Side	15"	(432 mm)
SFC	Side Wall to Flue Collar	23"	(635 mm)
BW	Back Wall to Side	15"	(305 mm)
BCF	Back Wall to Flue Connector	17"	(381 mm)

Chimney Connection


Use 6" flue connector made from 24 gauge or heavier steel.

Chimney Connector Clearances

The stove position will be determined by the greater of either the stove clearance or the chimney connector clearance above (X) and to the side (Y).

X Connector to Ceiling 19"
Y Connector to Parallel Wall 19"

Rear Exit Chimney Connector Clearance



Floor Protection

Any floor that is not composed of concrete poured on earth requires protection from sparks and embers. This stove is approved for installation using one of the following forms of hearth protection:

1. Any UL, ULC, or Warnock Hersey Listed Type 1 hearth board.
2. Any noncombustible material.

	A	B	C	D	E
U.S.	38 in.	8 in.	37 in.	16 in.	2 in.
	950 mm	200 mm	940 mm	400 mm	51 mm
CAN	38 in.	8 in.	45 in.	18 in.	2 in.
	950 mm	200 mm	1140 mm	460 mm	51 mm

